

# Specifications: iPF8300

Class	44-inch
Ink Type	Pigment inks 12 colours LUCIA EX: BK, MBK, C, M, Y, PC, PM, GY, PGY, R, G, B
Maximum Print Resolution	2,400 x 1,200dpi
Printing speed (A0 Roll, Full Colour Image)	1:58 (Draft Mode)
Plain Paper	3:39 (Standard Mode)
Coated Paper	3:39 (Standard Mode)
Glossy Photo Paper	7:15 (High Quality Mode)
	6:31 (Standard Mode)
	11:11 (High Quality Mode)
Dimensions, Weight (Net) W x D x H (mm), (kg)	Main unit with Printer Stand and Basket: 1,893 (W) x 975 (D) x 1,144 (H) mm, Weight: approx. 143 kg
Dimensions, Weight (Packaged) W x D x H (mm), (kg)	Main unit: 2,080 (W) x 1,060 (D) x 867 (H) mm; Weight: approx. 170kg Printer stand and Basket : 1,795 (W) x 863 (D) x 363 (H) mm; Weight: approx.43 kg
Power Supply	AC 100 - 240 V (50/60 Hz)
Input power	190 W or less
Power consumption	6 W or less
Standby power consumption (At the low power mode)	5 W or less
220 V - 240 V	1 W or less (In compliance with Executive Order of the President of the United States of America)
100 V - 120 V	Temperature: 15 - 30°C, Humidity: 10 - 80% (Condensation free)
Power off (standby)	Operation: 50 dB (A) or less (Glossy paper, Image, Print quality: Standard)
Operational Environment	Standby: 35 dB (A) or less (measured based on ISO7779 under the above conditions)
Acoustic Noise	Operation: 6.8 Bels or less (Glossy Photo paper, Image, Standard) (measured based on ISO7779 under the above conditions)
Acoustic pressure	384 MB
Acoustic power	No
Memory	GARO (Graphic Arts language with Raster Operations) Job control: CPCA, Status reply: CPCA, SNMP-MIB (Standard MIB, Canon MIB)
Standard Memory	Flash ROM
Expansion slot	Updated from USB, 1394, Ethernet port (Utility use)
Printer Language	Large LCD: 160 x 128 dots, LED x 5, Key x 13
Firmware Type	US-English, Japanese
Update	US-English, French, German, Italian, Spanish, Chinese, Korean, Russian, Japanese (Kanji)
Operation Panel Display	2.5 inch 80GB 5400 rpm S-ATA i/F
Language on operation panel	Built-in
Displayable Language on LCD	Full Speed (12 Mbit/sec), High Speed (480 Mbit/sec), Bulk transfer Series B (4 pins)
Hard disk	Built in
Interface	IEEE 802.3 10base-T, IEEE 802.3 100base-T / Auto-Negotiation, IEEE 802.3u 100base-TX / Auto-Negotiation, IEEE 802.3x Full Duplex IPX/SPX (Netware 4.2(J), 5.1(J), 6.0(I), SNMP (Canon-MIB), HTTP, TCP/IP (IPv4/IPv6), AppleTalk
Hi-Speed USB	Operating Systems supported
Type	Windows
Mode	2000 (32 bit), XP (32 / 64 bit), Vista (32 / 64 bit), Windows 7 (32 / 64 bit), Server 2003 (32 / 64 bit), Server 2008 (32 / 64 bit)
Connector type	Mac
Gigabit Ethernet	OSX (32 / 64 bit) 10.3.9 - 10.6
Type	
Standard	
Protocol	
PRINT HEAD	
Model	PF-05
Type	Bubble-jet on demand
Head configuration	6 colours integrated type (6 chips per print head x 2 print heads)
Nozzle pitch	1,200dpi x 2
Nozzle per chip	2,560 nozzles x 6 colours, 2 print heads
Droplet size	4 pl
Head replacement	User replacement
INK TANK	
Model	PFI-304/704: BK, MBK, C, M, Y, PC, PM, GY, PGY, R, G, B

CUTTER	
Model	Cutter Blade CT-06
Type	Automatic horizontal cutting (Rotary cutter)
Cutter durability (cuts)	1,500 cuts (Canvas or Cloth media types)
MEDIA HANDLING	
Roll paper	One roll, front-loading, front output
Cut sheet	Front loading, front output (manual feed using media locking lever)
Media Type	Standard Paper 80gsm, Standard Paper 90gsm, Matt Coated Paper 90gsm, Glossy Photo Quality Paper 190gsm / 240gsm / 300gsm, Satin Photo Quality Paper 190gsm / 240gsm / 300gsm, Pearl Photo Paper 260gsm, Matt Coated Paper 120gsm / 140gsm / 180gsm, Opaque White Paper 120gsm, High Resolution Self-adhesive Graphic Paper 140gsm, High Resolution Barrier Paper 180gsm, Glossy Proofing Paper 195gsm, Semi-Glossy Proofing Paper 195gsm / 255gsm, Water Resistant Art Canvas, Artistic Matte Canvas, Artistic Satin Canvas, Universal Opaque White Film, Roll-Up Film, Scrim Banner Vinyl, Scrim Banner, Adhesive Matte Vinyl, Adhesive Matt Vinyl Stretch.
Media Size	
Roll paper (width)	ISO: A3, A2, A1, A0 JIS: B2, B1, B0 ARCH: 24", 30", 36" Others: 10", 14", 16", 17", 42", 44"
Cut sheet	ISO: A4, A3, A3+, A2, A2+, A1, A0, B4, B3, B2, B1, B0 DIN: C4, C3, C2, C1, C0 JIS: B4, B3, B2, B1, B0 ANSI: 8.5 x 11", 8.5 x 14", 11 x 17", 13 x 19", 17 x 22", 22 x 34", 28 x 40", 34 x 44" ARCH: 9 x 12", 12 x 18", 18 x 24", 24 x 36", 26 x 38", 27 x 39", 30 x 42", 36 x 48" Photo: 20 x 24", 18 x 22", 14 x 17", 12 x 16", 10 x 12", 10 x 15", 8 x 10", 16 x 20" (US Photo size) Poster: 20 x 30", 30 x 40", 42 x 60", 44 x 62", 300 x 900mm Others: 13 x 22"
Media Thickness	Roll paper & Cut sheet: 0.07 - 0.8mm
Maximum Outside Diameter of Roll Paper	150mm
Media Core Size	Internal diameter of roll core: 2" / 3"
Media Width	Roll paper: 254mm - 1,117.6mm Cut sheet: 203.2 - 1,117.6mm
Minimum Printable Paper Length	203.2mm (8")
Maximum Printable Paper Length	Roll paper: 18m (Varies according to the OS and application) Cut sheet: 1.6m
Margins (Top, Bottom, Sides)	
Recommended area	Roll paper: Top: 20mm, Bottom: 5mm, Side: 5mm Cut sheet: Top: 20mm, Bottom: 23mm, Side: 5mm
Printable area	Roll paper: Top: 5mm, Bottom: 5mm, Side: 5mm Roll paper (borderless print): Top: 0mm, Bottom: 0mm, Side: 0mm Cut sheet: Top: 5mm, Bottom: 23mm, Side: 5mm
Media width for Borderless printing	515mm (JIS B2), 1,030mm (JIS B0), 594mm (ISO A1), 841mm (ISO A0), 10", 14", 17", 24", 36", 42", 44"
OPTION	
Media take-up unit	TU-06
Roll Holder set	RH2-44
CONSUMABLES	
Ink Tank	PFI-304 (330ml): BK, MBK, C, M, Y, PC, PM, GY, PGY, R, G, B PFI-704 (700ml): BK, MBK, C, M, Y, PC, PM, GY, PGY, R, G, B
Print Head	PF-05
Cutter Blade	CT-06
Maintenance Cartridge	MC-08
Some images are simulated for clarity of reproduction. All data is based on Canon's standard testing methods. This leaflet and the specifications of the product have been developed prior to the date of product launch. Final specifications are subject to change without notice. ® and ©: All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries. Canon recommends you use Canon Media for the best results. Please check media (paper) compatibility list to see which variety of paper/media is recommended.	



Canon Inc.  
www.canon.com

Canon Europa N.V.  
www.canon-europe.com

English-UK Edition  
© Canon Europa N.V., 2010 (0310)

Canon (UK) Ltd  
Woodhatch, Reigate  
Surrey RH2 8BF  
Telephone No: 01737 220000  
Facsimile No: 01737 220022  
www.canon.co.uk

Canon Ireland  
Arena Road, Sandyford  
Industrial Estate  
Dublin 18, Ireland  
Telephone No: 01 2052400  
Facsimile No: 01 2958141  
www.canon.ie